



ATEX version available



**The new X5
from infostream.**

**A rugged, industrial strength pager
designed for impossible situations.**

© 2006 - All rights reserved.

A perfect messaging solution for





The X5 has been designed with features and functions that specifically meet the needs of emergency services organizations, medical, mining, petrochemical and security industries.

Developed as a result of extensive end user research and field analysis, the X5 is an intrinsically safe pager that can operate, and be operated, in extremely harsh environments. Buttons are spaced and have positive tactile feedback for use with gloves and at 85dB (A), the X5 is one of the loudest pagers on the market today.

10 Way wall mounted bank charger / alarm enunciator panel.



Designed & Manufactured by Sigtec.



Product Specifications

| | |
|-------------------------------|--|
| Co - channel rejection: | -8dB |
| Adjacent channel selectivity: | >70dB |
| Baud rate: | 512,1200,2400 Baud |
| Signal format: | POCSAG CCIR RPC No. 1 |
| Safety: | Eex ib IIC T4 (IEC 60079) |
| Single charge operating time: | 10 days (typical) |
| Battery Type: | Rechargeable Li-ion Polymer |
| Alert loudness: | 85 dB(A) at 50 cm (typical) |
| Display: | 200 x 176 pixels 65,536 colours |
| Dimensions: | 91 x 51 x 20mm |
| Additional alerts: | Super bright red LED (array of 3 LEDs) |



Unit 12 Owenacurra Business Park
Knockgriffin, Midleton Co Cork
Ireland

Phone: +353 21 4633675

Email: info@sigtec.ie

www.sigtec.ie